

# Datasheet

# 4/8 ports VoIP Router

## VoIP Router

### Connect Port

- 4 / 8 x FXS Ports
- 1 x RJ-45 WAN Ethernet 10/100 Port
- 2 x RJ-45 LAN Ethernet 10/100 Ports

### Voice Processing

- Audio CODEC:
  - G.711 a-law / u-law
  - G.726
  - G.729
  - GSM
- Transparent pass through
- G.168 echo cancellation
- Carrier tone generation
- Silence suppression and comfort noise
- DTMF In/Out band Relay
- DTMF/ Call progress detection and generation

### Voice Signaling

- Support SIP v2.0 Standard (RFC3261)
- NAT Traversal
  - Outbound Proxy
  - STUN Server
- Register up to 4 Server simultaneously
- Support multiple dialing plan / Call hunting group
- Adaptive Jitter Buffer function
- Multiple call profile for different parameters

### Route Functions

- Support static and dynamic IP from DHCP, PPPoE
- Build-in DHCP Server
- Self-Protection against DoS Attacks
- Support NAT through function
- Supported Protocol: UDP, TCP, NAT, BOOTP, TFTP, FTP, HTTP, TELNET, IEEE 802.3/ IEEE 802.3u
- Support SNMP, SNTP, HTTP, FTP, NAT, DNS, DDNS
- NAT function: Virtual Server, Port mapping, Static routing table

- DoS: TCP/UDP PortScan, IP Land, PingOfDeath, ICMP Smurf, TCP SynWithData, UDP Bomb
- Support QoS (ToS & DSCP) and bandwidth control, reserve bandwidth for VoIP call when data traffic busy

### Fax Support

- T.38FAXRelay / T.30

### Management

- Web Interface Management
- WAN IP configure can be programmed by phone with IVR prompt
- Support Auto Provision Server
- Remotely configuration/Upgrade by Web UI or Auto Provision Server.
- Exportable CDR to CDR server
- Option support TR-069
- 1 Reset button for load default ID/Password.

### LED Indicators

- POWER, STATUS, READY, LAN, WAN, PHONE

### Power

- External AC Power Adapter
- 12V DC, 2A

### Humidity

- Up to 95% Non-Condensing

### Dimensions

- 200 x 120 x 36 mm (W/D/H)
- Weight : 0.5 Kg

### Warranty

- One Year Limited Warranty

### VoIP + Router!

FXS VoIP Gateway and Broadband Router

### SIP support!

Deploy into any multimedia, interactive, or softswitch network with the leading call and session signaling protocol

### Register up to 4 SIP Proxy & accounts mixable simultaneously!

Flexible registration for different VoIP Route plan

### Firewall, NAT, DHCP, PPPoE!


Connect to any broadband or access provider, serve the whole network, and secure your data. User configurable IP services ensure every host is connected to the LAN.

### Auto Provision Server!

Easy to remote configure/Upgrade via Provision System.

### WAN/LAN IP Setting by Phone!

Easy IP configuration by Phone



### Setup Web



SA980



SA940

### Model Information

SA940: 4FXS, 1WAN+2LAN

SA980: 8FXS, 1WAN+2LAN